

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007552 A1

(51) International Patent Classification⁷: **B66B 7/06**

(21) International Application Number:
PCT/US2003/019503

(22) International Filing Date: 20 June 2003 (20.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MONZON, Andres** [ES/ES]; Plaza Espana, 7-3 A, Leganes, E-28911 Madrid (ES). **CANALES, Jose** [ES/ES]; C. Federco Garci a Lorco, 21 Majadahonda (ES). **DEL RIO, Fernando**

[ES/ES]; Paseo Pascual Saorin, 17, Torreldones, E-28250 Madrid (ES). **SANZ, Francisco** [ES/ES]; C. Fuentespina, 2, E-28031 Madrid (ES). **ADIFON, Leandre** [BJ/US]; 35 Brentwood Drive, Farmington, CT 06032 (US).


(74) Agent: **OLDS, Theodore, W.**; Carlson, Gaskey & Olds, 400 West Maple, Suite 350, Birmingham, MI 48009 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: **COMPACT BEDPLATE WITH INTEGRATED, ACCESSIBLE DEAD END HITCHES**



(57) Abstract: An improved elevator mounts its dead end hitches (38A, 38B, 38C and 40A, 40B, 40C) on the bedplate (46, 48) of a machine roomless elevator. The dead end hitches are preferably positioned on an upper surface of the bedplate such that they are easily accessible. Further, the governor (80) is mounted adjacent the machine (24) on the bedplate. Preferably, there are a plurality of dead end hitches and a plurality of connecting members connecting the car and counterweight. The plurality of dead end hitches are preferably aligned along lines (A and B) which are parallel to a drive axis of the drive sheave (30). Further, the plural connecting members are preferably each associated with a surface on a drive sheave and a pair of dead end hitches. A line drawn through a sheave surface and its two associated dead end hitches would be perpendicular to the rotational drive axis.

WO 2005/007552 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.